



**HAYMAN**<sup>TM</sup>  
SAFE COMPANY

## CASHVAULT SAFE OPERATION GUIDE



### **“B” Rate Chest Key Features:**

- Bolt Detent
- ½” Solid Steel Door
- Electronic Lock Available in All Sizes
- 4 Bolt Down Holes Provided

### **Depository Safe Key Features:**

- Same Features as “B” Rates
- Front and Top Loaders
- Dual Compartment Safes Available
- Anti-Fish Baffles

# **CASHVAULT**

## **MECHANICAL SAFE LOCK**

### **OPERATING INSTRUCTIONS:**

1. Turn the dial counterclockwise (to the left) until the first number of your combination aligns with the 12 o'clock opening index 4 times, be sure to stop on the first number of your combination the fourth time.
2. Turn the dial clockwise (to the right) until the second number of your combination aligns with the 12 o'clock opening index 3 times, be sure to stop on the second number of your combination the third time.
3. Turn the dial counterclockwise (to the left) until the third number of your combination aligns with the 12 o'clock opening index 2 times, be sure to stop on the third number of your combination the second time.
4. Turn the dial clockwise (to the right) until the dial comes to a complete stop, and then turn the safe handle to gain access.
5. Locking your safe; Close the safe door and then spin the safe dial to the left at least 4 full turns.

If you do not successfully gain access repeat steps 1-4.

### **BOLT DOWN INSTRUCTIONS:**

#### **Steps:**

1. Place the safe in the location desired.

Note that it is desirable to have at least 1" clearance to the wall on the back and sides.

2. Mark the floor at the two front corners of the safe.

This will help in relocating the safe after drilling the mount holes in the floor.

3. From inside the safe, mark the floor through the mount holes in the bottom of the safe.
4. Move the safe to the side and drill the floor at the marks with the masonry drill bit. Be sure to drill the holes deeper than the length of the anchors.
5. Vacuum the concrete dust out of and from around the holes in the floor.
6. Move the safe back into position using the corner marks to help align the safe.
7. Insert the anchor through the safe floor and into the concrete floor until the washer touches the safe floor, and then tighten the nuts from inside the safe.
8. Tighten first to a barely snug level on each bolt before tightening up all bolts evenly.

#### **Tools You Will Need:**

- Drill Motor
- Anchors
- Masonry Drill Bit
- Wrench to fit nuts on anchors
- Marker to mark the floor

# **CASHVAULT**

## **ELECTRONIC SAFE LOCK**

### **OPERATING INSTRUCTIONS:**

Note:

\*SecuRam Locks have two factory default codes.

A Manager Code of 111111 and a Master code of 123456.

\*La Gard (LG) Locks have a factory default Master code of 123456.

All factory default codes *must* be changed before using your new safe.

To open your electronic lock, enter your 6 digit manager or master code.

The lock will beep twice indicating a correct code and the door can be opened.

If a wrong code is entered, the lock will beep three times indicating a wrong code.

If a wrong code is entered four times in a row, the lock will go into timeout mode for 5 minutes.

Wait for the timeout mode to expire and enter the correct code.

To change the Manager or Master code on either lock above:

1. Write down your new code.
2. Open the door with the existing code and extend the bolts.  
Perform all lock service with the door open.
3. Enter 000000 (lock beeps twice).
4. Enter existing code once (lock beeps twice).
5. Enter new code (lock beeps once).
6. Enter new code again to verify (lock beeps once).

Test the operation of the new code twice before closing the door.

Lastly, test the operation of the new code with the door closed.

For more detailed information on your SecuRAM SafeLogic lock visit

[www.securamsys.com](http://www.securamsys.com)

For more detailed information on your La Gard (LG) Basic Lock visit

[www.kaba-mas.co](http://www.kaba-mas.co)

Or for more information on these locks such as changing the batteries visit

YouTube and go to the HAYMAN Safe Co Network.

Use only **FRESH** Duracell or Eveready Alkaline 9V batteries in the lock keypad.

# **CASHVAULT**

## **DOUBLE KEY LOCK OPERATING INSTRUCTIONS:**

Insert the two keys into the keyholes with the cuts facing out.

Turn the key furthest from the leading edge of the door first and leave in the rotated position. Turn the key closest the leading edge of the door and open safe.



**HAYMAN**<sup>™</sup>  
**SAFE COMPANY**

## WARRANTY

### **ONE YEAR WARRANTY**

All Hayman Safe Company products carry a warranty to the original retail purchaser to be free from defects in material and workmanship. Standard models are warranted for ONE (1) year from the original date of purchase.

This warranty applies only to new safes purchased from Hayman Safe Company or its authorized dealers. Proof of purchase must be provided so as to establish date of purchase and supplying dealer.

Hayman Safe Company will, at our option, repair or replace any defective part or unit.

**Authorization must be received from Hayman Safe Company prior to performance of any service which will be submitted under warranty.**

Improper installation, improper use, lack of proper maintenance or accidental damage will nullify this warranty. No other warranty, expressed or implied, is offered. This warranty cannot be changed, modified, enlarged or altered without direct written consent from Hayman Safe Company.

Hayman Safe Company is not responsible for consequential damage, incidental expenses or personal injury.

This warranty gives you specific legal rights.

You may have other rights which vary from state to state.

## GUARANTEE

### **BURGLARY PROTECTION**

Hayman safe Company will, at our option, replace or repair any CashVault if they are ever successfully burglarized.

To claim this guarantee, ship the burglarized safe and copy of the police report to us. We will repair or replace the safe and return it to you.

Improper installation can nullify this guarantee.

### **HAYMAN SAFE COMPANY**

1291 N SR 426

Oviedo, FL 32765

[www.HaymanSafe.com](http://www.HaymanSafe.com)